

Amendments to the Claims:

This following listing of claims will replace all prior versions, and listings, of claims in the application.

Listing of Claims:

Claim 1 (previously presented): A method for transmitting a WDM signal:
modulating a first optical signal on a first wavelength with a first data signal having a first data rate to generate a first modulated optical signal having a first bandwidth;
modulating a second optical signal on a second wavelength with a second data signal having a second data rate to generate a second modulated optical signal having a second bandwidth, said second bandwidth being greater than said first bandwidth and said WDM signal comprising said first modulated optical signal and said second modulated optical signal; and
applying error correction coding to said first and second data signals such that said second data signal experiences a greater coding gain than said first data signal.

Claim 2 (canceled)

Claim 3 (canceled)

Claim 4 (canceled)

Claim 5 (original): The method of claim 1 wherein said first data signal comprises an OC-48 signal and said second data signal comprises an OC-192 signal.

Claim 6 (original): The method of claim 1 further comprising:
multiplexing said first modulated optical signal and said second modulated optical signal together to form said WDM signal.

Claim 7 (original): The method of claim 1 wherein said first modulated optical signal and said second modulated optical signal have substantially similar power levels when multiplexed together.

Claim 8 (canceled):

Claim 9 (previously presented): A method of receiving a WDM signal, said method comprising:

demodulating a first modulated optical signal derived from said WDM signal to form a first recovered data signal, said first modulated optical signal having a first bandwidth;

demodulating a second modulated optical signal derived from said WDM signal to form a second recovered data signal, said second modulated optical signal having a second bandwidth greater than said first bandwidth; and

decoding said first and second recovered data signals in accordance with error correction coding applied to first and second data signals wherein a lower signal to noise ratio of said second modulated optical signal is compensated for relative to said first modulated optical signal.

Claim 10 (canceled)

Claim 11 (canceled)

Claim 12 (canceled)

Claim 13 (original): The method of claim 9 wherein said first recovered data signal comprises an OC-48 signal and said second recovered data signal comprises an OC-192 signal.

Claim 14 (original): The method of claim 9 wherein said first modulated optical signal and said second modulated optical signal are received with substantially similar power levels.

Claim 15 (canceled):

Claim 16 (previously presented): A WDM transmission system comprising:
a first transmitter generating a first modulated optical signal that has been modulated with a first data signal;

a second transmitter generating a second modulated optical signal that has been modulated with a second data signal;

a first error correction coding block that applies an error correcting code to said first data signal prior to modulation; and

a second error correction coding block that applies an error correcting code to said second data signal prior to modulation so that a coding gain of said second modulated optical signal is greater than any coding gain of said first modulated optical signal.

Claim 17 (canceled)

Claim 18 (canceled)

Claim 19 (canceled)

Claim 20 (original): The WDM transmission system of claim 16 wherein a bandwidth of said second modulated optical signal is greater than a bandwidth of said first modulated optical signal.

Claim 21 (original): The WDM transmission system of claim 16 further comprising:
a first amplifier that amplifies said first modulated optical signal; and
a second amplifier that amplifies said second modulated optical signal, wherein amplified power levels of said first modulated optical signal and said second modulated optical signals are substantially similar.

Claim 22 (original): The WDM transmission system of claim 21 further comprising:
a multiplexer that combines said first modulated optical signal and said second modulated optical signal to form a WDM signal.

Claim 23 (original): The WDM transmission system of claim 21 wherein said first data signal comprises an OC-48 signal and said second data signal comprises an OC-192 signal.

Claim 24 (previously presented): A WDM receiver system comprising:
a first optical receiver that recovers a first recovered data signal from a first modulated optical signal on a first wavelength;
a second optical receiver that recovers a second recovered data signal from a second modulated optical signal on a second wavelength;
a first error correction decoding block that decodes said first recovered data signal in accordance with an error correcting code imposed on data of said first recovered data signal; and
a second error correction decoding block that decodes said second recovered data signal in accordance with an error correcting code imposed on data of said second recovered data signal, said error correcting code of said second error correction decoding block compensating for a lower signal to noise ratio of said second modulated optical signal compared to said first modulated optical signal.

Claim 25 (original): The WDM receiver system of claim 24 wherein said first recovered data signal comprises an OC-48 signal and said second recovered data signal comprises an OC-192 signal.

Claim 26 (canceled)

Claim 27 (original): The WDM receiver system of claim 24 wherein said second modulated optical signal has a greater bandwidth than said first modulated optical signal.

Claim 28 (canceled)

Claim 29 (canceled)

Claim 30 (canceled)

Claim 31 (original): The WDM receiver system of claim 24 wherein said first modulated optical signal and said second modulated optical signals are received with substantially similar power levels.

Claim 32 (previously presented): Apparatus for transmitting a WDM signal:

- means for modulating a first optical signal on a first wavelength with a first data signal having a first data rate to generate a first modulated optical signal having a first bandwidth;
- means for modulating a second optical signal on a second wavelength with a second data signal having a second data rate to generate a second modulated optical signal having a second bandwidth, said second bandwidth being greater than said first bandwidth and said WDM signal comprising said first modulated optical signal and said second modulated optical signal;
- means for applying error correction coding to said first data signal; and
- means for applying error correction coding to said second data signal so that said second data signal experiences a greater coding gain than said first data signal.

Claim 33 (previously presented): An apparatus for receiving a WDM signal comprising:

- means for demodulating a first modulated optical signal derived from said WDM signal to form a first recovered data signal, said first modulated optical signal having a first bandwidth;
- means for demodulating a second modulated optical signal derived from said WDM signal to form a second recovered data signal, said second modulated optical signal having a second bandwidth greater than said first bandwidth;
- means for decoding said first recovered data signal; and
- means for decoding said second recovered data signal in accordance with an error correction coding scheme wherein said error correction coding scheme of said second recovered data signal compensates for a lower signal to noise ratio of said second modulated optical signal relative to said first modulated optical signal.